

new atlas

GN 1/1 freezer counter – Depth 700



The new range of "NEW ATLAS" freezer and refrigerated tables, available with a depth of 600 mm or 700 mm, is designed and manufactured to the highest quality standards.



The tables are provided with electrical defrosting system by heating elements and with a device for automatic elimination of condensate water.

They are also available with built-in condensing unit or prearranged for a remote condensing unit with a valve system, in a normal and low temperature solution.

Equipped with 1, 2, 3 or 4 doors, with the possibility of installing drawer units with 2 or 3 drawers. Accessories provided: 1 GN 1/1 rack per door.

Prearranged to be installed on plinth.

Counters available with 10/10 thickness stainless steel normal worktops or with rear riser.



TECHNICAL DATA:

		TGB7D/170		TGB7S/170	
Body	mm	660		660	
External dimensions without worktop TGB7D(S)/...S (WxDxH)	mm	1750x690x810		1750x690x810	
External dimensions with normal worktop TGB7D(S)/...			1760x700x850		1760x700x850
External dimensions with worktop with rear riser TGB7D(S)/...A				1760x700x950	1760x700x950
Capacity	lt	410		243	
Technical compartment position		right		left	
Doors	nr	3		3	
Evaporators	nr	2		2	
Equipment (GN 1/1 shelves)	nr	3 GN 1/1		3 GN 1/1	
Control panel		digital control by back panel		digital control by back panel	
Cooling system		ventilated		ventilated	
Temperature	°C	-15/-20		-15/-20	
Defrosting system		automatic by heating elements		automatic by heating elements	
Condensate water elimination		automatic		automatic	
Max absorbed power *	W	655		655	
Cooling power **	W	695		695	
Gas		R290		R290	
Input voltage		1x230V/50Hz		1x230V/50Hz	
Climatic class		5		5	

*Evap. -10°C cond. +45°C - **ASHRAE (Evap. -23.3°C cond. +54.4°C)



Internal detail



Back panel control board




Drawer detail



Detail of s/s worktop edge

ACCESSORIES AND SURCHARGES ON REQUEST:



CR7/2BT Freezer drawer unit with 2 1/2 drawers (surcharge)



Pair of runners for GN 1/1



GN 1/1 shelf

GN 1/1 s/s shelf



Set of Ø 125 castors



Wi-Fi supervising system (surcharge)



60Hz Voltage

INSTALLATION DIAGRAM:

